

- MATERIALS:
- ARMOR CAST POLYMER CONCRETE METER BOX AND LID.

   A. 3/4" OR 1" SERVICE 13"X24"X12" BODY NO. A6001946PCX12 20K AND CAST IRON READ COVER NO. A6001969RC1 20K.
- 2. 1" MUELLER CORP. STOP PN B25028N
- 3. 1" CTS SDR 9 (200 PSI) PE BLUE. USE SS STIFFENER FOR FITTINGS PN504385 TUBING OR SOFT TEMPER, TYPE 'K' COPPER TUBING COMPLYING WITH ASTM B-88 UPON ENGINEERS APPROVAL.
- 4. 1" MUELLER ANGLE METER STOP PN B24258N CMP CTS X MTR
- 5. 1" MUELLER ANGLE METER STOP PN B24265N FIP X MTR (CUSTOMER SIDE)
- 6. 3/4" TO 1" BRASS METER ADAPTER FORD PN A-34NL OR APPROVED EQUAL (FOR 3/4" METER INSTALLATIONS)
- 7. 14GA. BLUE DIRECT BURIAL TRACER LOCATE WIRE, SOLID CORE MIN. .045 INSULATED COVER.

## NOTES:

- 1. SUBSTITUTES FOR ANY MATERIALS SHOWN SHALL BE APPROVED BY THE CITY ENGINEER.
- 2. ALL PIPE AND STRUCTURE ZONES SHALL BE BACKFILLED USING 3/4" MINUS CRUSHED
- AGG. AND COMPACTED TO 95% MAX. DENS. AS DETERMINED BY AÁSHTO T-180.
- 3. METER BOX SHALL BE CENTER OVER THE COMPLETED METER ASSEMBLY.
- 4. WATER METERS THAT ALSO PROVIDE FIRE SUPPRESSION MUST BE TAGGED WITH "SUPPLIES FIRE SUPPRESSION." TAG SHALL BE MIN. 2.5" X 5", WEATHERPROOF, HEAVY DUTY RED PLASTIC. PRE-DRILL AND SECURED TO THE METER WITH PLASTIC CABLE TIES.
- 5. SERVICE SADDLES MANUFACTURED FOR USE WITH HDPE PIPE SHALL BE USED WHEN CONNECTING TO HDPE MAINS.
- 6. NEW SERVICES TO 3/4" METERS SHALL BE 1" PE BLUE TUBING.

* Providence *	1095 Duano Stroot	3/4" & 1" Water Service Detail				
		Date Adopt.	11/01/2012	Date Rev.	08/07/2023	DWG. NO.
		Dwg. Name: W-3 1 Inch Water Service.dwg				W-3